


USING MATLAB FOR MATERIALS DESIGN: DESCRIBING GRAIN ORIENTATIONS IN METALS



Claes Olsson, PhD - Docent / Sandvik Materials Technology



THE SANDVIK GROUP



MACHINING SOLUTIONS



MINING AND
CONSTRUCTION



MATERIALS
TECHNOLOGY



SANDVIK MATERIALS TECHNOLOGY


THE STEEL RESEARCH CENTER IN SANDVIKEN

- ~ 230 staff
- ~ 900 different materials
- Steels
 - Ni-base
 - Zircaloy
 - Titanium
 - Powder Metallurgy
 - Thin Film Coatings
 - ...

ANALYTICAL TASK

- Zircaloy tubes are used for packaging nuclear fuel
- To prevent cracking, it is important to control grain orientation in the tube wall.
- Grain orientation is characterized with X-ray Diffraction
- Data evaluation, quantification and reporting is made with MATLAB + MTEX
- MTEX is an open source toolbox, developed by Prof. Dr. Ralf Hielscher *et al.* at TU-Chemnitz. It contains tools for handling material orientation data:

<https://mtex-toolbox.github.io/>



ZIRCALOY
TUBING FOR NUCLEAR FUEL



NUCLEAR FUEL RODS IN ZIRCALOY


CHARACTERISTICS

- Right in the reactor core
- Need a material with low neutron capture cross section, hence Zr-Nb alloys
- Good control of impurities
- High demands on the metallurgical process
- High demands on the rolling process


Uranium pellet:
Weight: 7 to 8 g
Height: 10 to 15 mm
Width: 8 to 9 mm




Fuel rod:
Weight: 2,2 kg
Length: 4 m
Width: < 1 cm
contains about 300 pellets




Fuel assembly:
Weight: 800 kg (including 600 kg uranium oxide)
Height: > 5 m
Width: 21 cm x 21 cm
17 x 17 rods



ROLLING TUBES OF HEXAGONAL MATERIALS






TEXTURE MEASUREMENT WITH X-RAY DIFFRACTION (XRD) AND MATLAB




THE ORIENTATION DISTRIBUTION FUNCTION (ODF)

Orientation Distribution (Euler Angles)

- Describes the orientation of all crystals in the sample
- For a cubic system, a $90^\circ \times 90^\circ \times 90^\circ$ space is sufficient
- $\frac{dV}{V} = f(g)dg = f(\varphi_1, \Phi, \varphi_2) \frac{\sin\Phi}{8\pi^2} d\Phi d\varphi_1 d\varphi_2$



X-Ray Diffraction Measures Lattice Spacing




- Only crystals with the correct orientation fulfill the Bragg condition, i.e.

$$\Delta \mathbf{k} = \mathbf{G} \quad , \text{ alternatively}$$


$$d = \frac{2 \sin \theta}{n \lambda}$$

- Record the intensity of each diffraction peak in a 5°x 5° grid on the hemisphere above the sample.

SPHERICAL PROJECTIONS



FAST DIFFRACTOGRAM RECORDING



New method: Extract intensities by curve fitting!

SYNTHETIC LINE PROFILES – PSEUDO VOIGT

$$I(2\theta) = I_{max} \left[m e^{-4 \ln 2 \left(\frac{2\theta - p}{w} \right)^2} + \frac{1 - m}{1 + 4 \left(\frac{2\theta - p}{w} \right)^2} \right]$$

where


I_{max} – peak height

p – peak position

w – full width at half max


m – Gauss / Lorentz mix

2θ – Scale for the x-axis




MULTI-PEAK FITTING

No tilt –
diffraction vector normal to
sample surface.
OK without fitting.




High tilt –
diffraction vector grazing to
sample surface.
Peak fitting necessary!



MULTI-PEAK FITTING

- Fix positions relative to each other
- Same width for all peaks
- Set the peak shape to Gaussian
- Intensity is the only completely free variable



Problem: Pass x fit variables and $(n-x)$ fix variables to the solver.

Solution:

- Create a peak shape function:

```
function a = voigtNpeaks(p, xData, fitNdx, fixNdx, fixPrms, nPeaks)
```

- Pass it to the solver (1 peak example):




```
fitNdx = [1 2];  
fixNdx = [3 4];  
fixPrms = [0.9 1];  
fitPrms = [1000 43 0.9 1];
```

```
newFitPrms = lsqcurvefit(@voigtNpeaks, fitPrms(fitNdx), x, y, ...  
lb(fitNdx), ub(fitNdx), opt, fitNdx, fixNdx, fixPrms, region.nPeaks);
```

- Finally, re-create the parameter vector inside the peak shape function:

```
p(fitNdx) = fitPrms;  
p(fixNdx) = fixPrms;
```

SPHERICAL PROJECTIONS



MTEX CODE SAMPLE – PLOTTING

```
% Set plotting convention
plotx2north;


% Define crystal plane(s)
hkls = { ...
    Miller(0, 0, 0, 2, cs), ...
};

%Define the grid
r = vector3d('polar', theta, psi);

% Crystal symmetry, Zr
cs = crystalSymmetry('6/mmm', [3.225 3.225 5.225], 'X||a*', 'Y||b', 'Z||c');



% Specimen symmetry
ss = specimenSymmetry('-1');

% Create and plot a pole figure
pf = PoleFigure(hkls{1}, r, poleInts(:, i), 'CS', cs, 'SS', ss);
plot(pf({2}));
```



<https://mtex-toolbox.github.io/>


MEASUREMENT - THEORY




Calculated From Measurements via the ODF



Measured Intensities




Calculated Intensities



Extracted Line Profile

Kearn's vector:
[0.52 0.33 0.16]




REPORTING

MATLAB Advantages:

- Need complete pole figure to calculate custom KPI:s
- Through *mtex-ODF*, we have access to full pole figures.
- Possibility to run the integrated intensities method in a complete evaluation script with the *Publish* function.
- To our knowledge, no commercial implementation exists of the integrated intensities approach.





EBSD

ELECTRON BACKSCATTER DIFFRACTION






SCANNING ELECTRON MICROSCOPY - ELECTRON BACKSCATTER DIFFRACTION

Each pixel in the image is a Kikuchi pattern


Automatic indexing of each pixel

The indexing gives the orientation of the grain in each point

These orientations are then exported to MATLAB.




MATLAB EBSD MAPPING




Identify grains:
Colorize pointwise by orientation

Colorize grains by orientation spread



Grain size histograms:





EXTRACT POLE FIGURES

EBSD compares well with XRD data,
although XRD samples a much larger area

Bonuses:

Lateral information

Possibility to extract information on individual grains



RECRYSTALLIZED FRACTION

A compound criterion for recrystallization:

$$(A > A_{crit}) \text{ AND } (GOS < GOS_{crit})$$


A = Grain Area

GOS = Grain Orientation Spread

The underlying gray scale is by bone-gray
by grain size.

This type of combined evaluation criteria is
very easily implemented in MATLAB.

In this case, RexFrac (yellow) = 35%



WHY MATLAB / MTEX?

- MTEX provides the Orientation Distribution Function
 - Easier (and better) than coding the spherical harmonics approximation ourselves.
- MTEX User Community within the Sandvik Group
- Compared to vendor specific software:
 - The integrated intensities method by curve fitting is not available commercially.
 - Access to many mathematical and plotting tools within the environment.

CONCLUSIONS

- MATLAB / MTEX was used for
 - Automated curve fitting, typically >10 000 fits / measurement
 - Creating a custom script for calculating Key Performance Indicators for Zircaloy tubing.
 - Scripted EBSD evaluation with complex criteria.